



Water Tight Technologies, LLC
P.O. Box 899
Payson, AZ 85547
www.britenez.com

Product Data Sheet

TPO General Purpose Caulk

Description:

BRITE-n-EZ™ General Purpose Caulk is a high quality sealant with excellent adhesion used in conjunction with *BRITE-n-EZ™* TPO systems as a fastener sealer, termination bar caulk, and TPO cut edge/seam edge treatment. This caulk can be used in non-roofing applications not specifically associated with the initial installation of the roofing system. This sealant can be used to caulk or seal sheet metal, masonry, brick and concrete block.

Physical Properties:

PROPERTY	PHYSICAL PROPERTIES
Color	White paste
Hazardous Components	Solvent Naptha (petroleum), light aliphatic (VM&P) – (CAS# 64742-89-8)
Specific Gravity	1.176
Solids Content	67.92%
VOC	Less than 338 grams / liter
Flash Point	10°C; 50° F
Weight	9.79 lbs / gal.

Application Instructions:

Surface to which *General Purpose Caulk* is applied must be clean, dry and free from loose and foreign materials, oils and grease. Apply caulk as follows:

- Clean Seam Step Off:** Wearing solvent protective gloves, using a clean cotton cloth or synthetic sponge, clean the entire length of the seam edge with *Brite-n-EZ™ Membrane Cleaner*. Allow *Membrane Cleaner* to flash-off.
- Apply Caulk:** Apply a bead of *General Purpose Caulk* ¼" thick by ¼" wide, centering the bead directly over the cleaned seam edge.
- Care Must Be Taken Not to Disturb Freshly Applied General Purpose Caulk**

Product Data:

Available Sizes: 10.1 oz tubes

Carton Size: 25 tubes per carton

Coverage: 1/4" thick wide bead is 20 -25 linear feet per tube.

Storage: Store in cool, dry well ventilated facility away from all ignition sources and direct heat. Protect from electrostatic charges. Keep containers closed when not in use.

Shelf Life: The shelf life is approximately 24 months if stored in original unopened containers at temperatures between 60° and 90°F. **ROTATE STOCK.**

Precautionary Data:

This product is flammable. Vapors may cause flash fires. Vapors may ignite explosively under certain conditions. Keep away from fire, sparks, and sources of heat. Do not smoke. Close container after use. Product may cause possible skin irritations and/or allergic sensitivity.

Do not allow product to reach sewage system or any water course.

For professional/industrial use only.

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects, or other reproductive harm.