



Water Tight Technologies, LLC
P.O. Box 899, Payson, AZ 85547



SECTION 1 – PRODUCT IDENTIFICATION

Product Name: BRITE-n-EZ™ White Reflective Coating	Manufacturer's Name: Water Tight Technologies, LLC
Item Number(s): SAWC1; SAWC5	Manufacturer's Address: P.O. Box 899, Payson, AZ 85547
24 Hour Emergency Telephone Number: CHEMTREC – United States 800-424-9300 ; International 202-483-7616 (collect)	HMIS Acute Hazard Rating: Health 1, Flammability 0, Reactivity 0
Chemical Name/Synonyms: N/A	Chemical Family: Mixture

SECTION 2 – CHEMICAL COMPOSITION


Ingredient Components (chemical names) Common Names Hazardous components 1% or greater Carcinogens 0.1% or greater	%	Case No.	OSHA PEL-TWA	ACGIH TLV-TWA
Ethylene Glycol	0-2	107-21-1	N/A	50 ppm
Barium Metaborate	0-4	13701-59-2	N/A	.05mg/m³
Silica Quartz (as dust)	0-0.15	14808-60-7	N/A	.1 mg/m³
Amorphous Silica (as dust)	0-0.6	7631-86-9	N/A	10 mg/m³
Proprietary Polymers and Other non-hazardous ingredients	> 58	N/A	N/A	N/A
Water	>35	732-18-5	N/A	N/A
Total	100			

SECTION 3 – PHYSICAL & CHEMICAL CHARACTERISTICS

Appearance/Odor: Odorless liquid, standard color is white	Physical State: Liquid	Solubility in Water: N/A
Boiling Point: 212° F	Specific Gravity (H ₂ O=1) 1.03	Melting Point: N/A
Vapor Pressure: @ 20° C (68° F): 17.5 mm Hg	Additional Information: % of water volume > 35	Freezing Point: Not Established
Volatiles: (% Wt or % Vol) 40%	Ignition Temperature: N/A	Reactivity in Water: N/A
Vapor Density (Air=1) < 1	Evaporation Rate: (Butyl Acetate=1) < 1	



Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547



SECTION 4- FIRE & EXPLOSION HAZARD DATA


Flash Point: N/A	Flammable Limits (in air): LEL: 0.9
Extinguishing Media: Dry product may burn. Use water, foam, chemical or CO2 extinguisher.	Fire Fighting Procedures: None established
Hazardous Decomposition Products: Burning, including when heated by welding or cutting will produce smoke, Carbon Dioxide, Carbon Monoxide. Dried solids can burn and release toxic fumes/ vapors.	Special Fire & Explosion Hazards: None
Method Used: Not Established	Auto-Ignition Temperature: This product is not self-igniting.

SECTION- 5 HEALTH HAZARD DATA

Effects of Overexposure: Medical Conditions Aggravated By Exposure Toxic fumes may be released during fire. Exposure to fumes may aggravate pre-existing eye, lung, and skin conditions.	Signs and Symptoms of Exposure: Dizziness, nausea or vomiting. Sensitive individuals may exhibit eye, nose, throat or dermal irritation with prolonged exposure to processing fumes or vapors.
Acute: Irritation to eyes, lungs, and mucous membranes	
Chronic: None known	
Emergency & First Aid Procedures: Eye Contact: Flush with water and call physician Skin Contact: Clean with soap and water. Inhalation: Remove to fresh air. Administer oxygen or artificial respiration, if necessary. Call physician. Ingestion: Consult a Physician. Primary Route of Entry: Inhalation, eyes, skin, ingestion	



Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547




SECTION 6 – REACTIVITY DATA	
Stability: Stable at ambient temperatures and pressures	Incompatibility: None known
Hazardous Decomposition Products: None known	Hazardous Polymerization: NA
Conditions to Avoid: None known	

SECTION 7 - SPILL OR LEAK PROCEDURES
Steps to be taken in case material is released or spilled: Small spill: Absorb using inert material. Use non-sparking tools. Transfer into secure containers for proper disposal. Use personal protective equipment as outlined below.
Large Spill: Ventilate confined spaces. Keep product out of watercourses by diking.
Waste Disposal Method: Dispose of as a hazardous waste in accordance with EPA/RCRA regulations 40CFR261 21(a) (1) Ignitability: D001

SECTION 8 – SPECIAL PROTECTION	
Respiratory Protection: Use NIOSH-Certified respiratory protection for organic vapor if necessary.	Eye Protection: Impervious glasses recommended
Protective Gloves: Impervious gloves are recommended to prevent skin contact.	Other Protective Equipment: Under normal application conditions, protective glasses, gloves, and clothing are adequate.
Ventilation: Provide adequate ventilation to maintain airborne concentrations below OSHA PELs.	



Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547



SECTION 9 – SPECIAL PRECAUTIONS OR OTHER COMMENTS

Storage/Handling:

Store in cool, dry, well ventilated facility, away from direct sun light. Store and use away from all sources of direct heat and ignition. Keep containers closed when not in use. Do not freeze.

Other Precautions:

Provide adequate ventilation and avoid prolonged or repeated contact with the skin. Wash with soap and water after contact.

Work/Hygienic Practices:

Maintain good personal hygiene practices. Wash contaminated clothing before reuse. Do not eat, drink, or smoke in work areas. Wash exposed skin before eating, drinking, smoking, or applying cosmetics.

SECTION 10 - TRANSPORTATION

Regulatory Agency:

U.S.A., DOT, IMO

Identification Number:

N/A

Proper Shipping Name:

Not regulated

Labels Required:

N/A

Hazard Classification:

N/A

Other Requirements:

Packing Group:

SECTION 11 – MISCELLANEOUS INFORMATION

Additional Comments:

None

Date of Previous MSDS:

Changes Since Previous MSDS:

Telephone Number for Additional Information:

888-269-2122

DISCLAIMER

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information is accurate, complete, or representative. Water Tight Technologies, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons if reasonable safety procedures are not followed.