




Water Tight Technologies, LLC
P.O. Box 899, Payson, AZ 85547



SECTION 1 – PRODUCT IDENTIFICATION

Product Name: SEBS Flashing Compound	Manufacturer's Name: Water Tight Technologies, LLC
Item Number(s): BRITE-n-EZ - SEBSF	Manufacturer's Address: P.O. Box 899, Payson, AZ 85547
24 Hour Emergency Telephone Number: CHEMTREC – United States 800-424-9300 ; International 202-483-7616 (collect)	HMIS Acute Hazard Rating: Health __, Flammability __, Reactivity __
Chemical Name/Synonyms: N/A	Chemical Family: Mixture

SECTION 2 – CHEMICAL COMPOSITION

Ingredient Components (chemical names) Common Names Hazardous components 1% or greater Carcinogens 0.1% or greater	%	Case No.	OSHA PEL-TWA	ACGIH TLV-TWA
Toluene*	40	108-88-3	200 ppm	100 ppm
Titanium Dioxide*	13	13463-67-7	5 mg/m³	5 mg/m³
Solvent		64742-95-6	100 ppm	N/A
Calcium Carbonate		1317-65-3	5 mg/m³	5 mg/m³
Styrene Butylene Block Copolymer		66070-58-4	NA	NA
Zinc Dibutyldithiocarbamate		136-23-2	NA	NA
Polyalicyclic Resin		69430-35-9	NA	NA


* Indicates toxic chemical subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION 3 – PHYSICAL & CHEMICAL CHARACTERISTICS

Appearance/Odor: White mastic, slight solvent odor.	Physical State: Liquid	Solubility in Water: Negligible
Boiling Point: 231° F	Specific Gravity (H ₂ O=1) 1.0	Melting Point: N/A
Vapor Density: Heavier than air	Additional Information: Evaporation rate – slower than ether	Freezing Point: Not Established
VOC: 3.24 lb/gal. (388 g/L)	Ignition Temperature: N/A	Reactivity in Water: N/A



Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547



SECTION 4- FIRE & EXPLOSION HAZARD DATA


Flash Point: 145° F	Flammable Limits (in air): LEL: 1.0%; UEL: 7.0%
Extinguishing Media: Foam, dry chemical or CO2 extinguisher.	Fire Fighting Procedures: Self-contained breathing apparatus with full face piece operated in pressure demand or other positive pressure mode. During emergency conditions over exposure to decomposition products may cause immediate or delayed health hazards.
Hazardous Decomposition Products: May form toxic materials, CO₂, CO, various hydrocarbons, etc. on thermal decomposition.	Special Fire & Explosion Hazards: Vapors are heavier than air and may travel along the ground and be ignited by heat, open flame, or other ignition sources. Keep containers tightly closed. Closed containers may explode when exposed to extreme heat.
Method Used: TCC	Auto-Ignition Temperature: This product is not self-igniting.

SECTION- 5 HEALTH HAZARD DATA

Medical Conditions Aggravated By Exposure: None known.	Signs and Symptoms of Exposure: Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, fatigue, nausea, headache and possible unconsciousness. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Eye contact may cause redness, tearing and blurred vision. Repeated skin contact may cause irritation, defatting and dermatitis.
Acute: Irritation to eyes, skin, nasal and respiratory irritation. Eye contact can cause redness and blurred vision. Skin contact may cause defatting and dermatitis. Aspiration into lungs can cause chemical pneumonitis, which can be fatal.	Chemical Listed as a Carcinogen (or Potential Carcinogen): National Toxicology Program: None I.A.R.C. Monographs: Toluene (108-88-3) OSHA: None
Chronic: Prolonged or repeated exposure to levels above TLV may result in permanent brain and nervous system damage.	
Emergency & First Aid Procedures: Eye Contact: Flush with water and call physician Skin Contact: Clean with soap and water. Remove contaminated clothing. Inhalation: Remove to fresh air. Administer oxygen or artificial respiration, if necessary. Call physician. Ingestion: Drink 1 – 2 glasses of water to dilute. Do not induce vomiting. Consult a Physician. Primary Route of Entry: Inhalation, eyes, skin, ingestion	



Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547



SECTION 6 – REACTIVITY DATA

Stability: Stable at ambient temperatures and pressures	Incompatibility: Avoid contact with strong oxidizing agents, strong acids and selected amine.
Hazardous Decomposition Products: May form toxic materials, CO₂, CO, various hydrocarbons, etc. on thermal decomposition.	Hazardous Polymerization: Will not occur
Conditions to Avoid: Do not expose to high temperatures, open ignition sources which induce thermal decomposition.	

SECTION 7 - SPILL OR LEAK PROCEDURES


Steps to be taken in case material is released or spilled: Small spill: Eliminate all ignition sources. Dike, contain or absorb with inert materials (sand, vermiculite, etc). Transfer containers for recovery or disposal. Prevent runoff into sewers, streams or other bodies of water.
Large Spill: Eliminate all ignition sources. Dike, contain or absorb with inert materials (sand, vermiculite, etc). Transfer containers for recovery or disposal. Prevent runoff into sewers, streams or other bodies of water.
Waste Disposal Method: Dispose of in accordance with federal, state and local regulations. Do not dump into sewers, on the ground or into any body of water.

SECTION 8 – SPECIAL PROTECTION

Respiratory Protection: If TLV is exceeded use NIOSH/MSHA approved organic vapor and mist mask, supplied air or self contained breathing apparatus, depending on the vapor concentration in the area. Do not enter area if vapor concentration exceeds OSHA permissible levels.	Eye Protection: Splash goggles or other OSHA permitted safety glasses.
Protective Gloves: Impervious gloves are recommended to prevent skin contact, i.e. nitrile rubber gloves.	Other Protective Equipment: Impervious clothing and supply eyewash stations.
Ventilation: Use adequate mechanical ventilation to maintain exposure to below TLV.	



Water Tight Technologies, LLC
P.O. Box 899, Payson, AZ 85547



SECTION 9 – SPECIAL PRECAUTIONS OR OTHER COMMENTS

Storage/Handling:

Store in cool, dry, well ventilated facility, away from direct sun light. Store and use away from all sources of direct heat and ignition. Keep containers closed when not in use. DO NOT FREEZE.

Other Precautions:

Provide adequate ventilation and avoid prolonged or repeated contact with the skin. Wash with soap and water after contact. Vapors of this product are heavier than air and will collect in confined areas. Do not take internally. Avoid breathing vapors.

Work/Hygienic Practices:

Maintain good personal hygiene practices. Wash contaminated clothing before reuse. Do not eat, drink, or smoke in work areas. Wash exposed skin before eating, drinking, smoking, or applying cosmetics.

SECTION 10 - TRANSPORTATION

Regulatory Agency:

Identification Number:

N/A

Proper Shipping Name:

Not regulated

Labels Required:

N/A

Hazard Classification:

N/A

Other Requirements:

Packing Group:

SECTION 11 – MISCELLANEOUS INFORMATION

Additional Comments:

This product contains chemicals (Toluene – CAS# 108-88-3) known to the state of California to cause birth defects or other reproductive harm

Date of Previous MSDS:

Changes Since Previous MSDS:

Telephone Number for Additional Information:

888-269-2122

DISCLAIMER

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information is accurate, complete, or representative. Water Tight Technologies, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons if reasonable safety procedures are not followed.