




Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547



SECTION 1 – PRODUCT IDENTIFICATION

Product Name: Rust Converter	Manufacturer's Name: Water Tight Technologies, LLC
Item Number: BRITE-n-EZ -- RC	Manufacturer's Address: P.O. Box 899, Payson, AZ 85547
24 Hour Emergency Telephone Number: CHEMTREC – United States 800-424-9300 ; International 202-483-7616 (collect)	HMIS Acute Hazard Rating: Health 2, Flammability 0, Reactivity 0
Chemical Name/Synonyms: N/A	Chemical Family: Mixture

SECTION 2 – CHEMICAL COMPOSITION


Ingredient Components (chemical names) Common Names Hazardous components 1% or greater Carcinogens 0.1% or greater	%	Case No.	OSHA PEL-TWA	ACGIH TLV-TWA
Tannic Acid		1401-55-4	N/A	N/A
2-Methoxyethoxy - ethanol		111-77-3	N/A	1 mm vapor pressure
Barium Sulfate		7727-43-7	5 mg / m³	10 mg/m³

SECTION 3 – PHYSICAL & CHEMICAL CHARACTERISTICS

Appearance/Odor: Opaque Liquid	Physical State: Liquid	Solubility in Water:
Boiling Point: 212° F	Specific Gravity (H ₂ O=1) 1.34	Melting Point: N/A
Vapor Pressure: 17.5 mm Hg	Vapor Density: < 1	Freezing Point: Not Established
Volatiles: (% Wt or % Vol) 62.0%	Other Information: N/A	Reactivity in Water: N/A



Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547



SECTION 4- FIRE & EXPLOSION HAZARD DATA

Flash Point: 200° F	Flammable Limits (in air): LEL: 1.5
Extinguishing Media: Carbon dioxide, dry chemical, alcohol foam	Fire Fighting Procedures: Vapor composition may be irritating to respiratory tract. Wear full face, self-contained breathing apparatus & impervious hood, suits, gloves.
Hazardous Decomposition Products: Oxides of carbon, nitrogen and hydrocarbons and hydrogen bromide (thermal degradation products)	Special Fire & Explosion Hazards: Dry product may burn. Use water, foam, chemical or carbon dioxide.
Method Used: PMCC	Auto-Ignition Temperature: This product is not self-igniting.

SECTION- 5 HEALTH HAZARD DATA

Permissible Exposure Limit: Not Established for this mixture	Signs and Symptoms of Exposure: Sensitive individuals may exhibit eye, nose, throat or dermal irritation with prolonged exposure to processing fumes or vapors.
Effects of Overexposure: Medical Conditions Aggravated By Exposure - Toxic fumes may be released during burning of dry product. Exposure to fumes may aggravate pre-existing eye, lung, and skin conditions.	
Acute: Irritation to eyes, lungs, and mucous membranes	Chemical Listed as a Carcinogen (or Potential Carcinogen):
Chronic: Irritation to eyes, lungs, and mucous membranes	National Toxicology Program: None I.A.R.C. Monographs: None OSHA: None

Emergency & First Aid Procedures: Symptoms of poisoning may even occur after several hours, therefore medical observation for at least 48 hours after the accident should occur.

Eye Contact:

Flush with water and call physician

Skin Contact:

Immediately wash with soap and water and rinse thoroughly.

Inhalation:

Remove to fresh air. Administer oxygen or artificial respiration, if necessary.

Ingestion:


Seek medical treatment.

Primary Route of Entry:

Inhalation, skin, eyes, ingestion.



Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547



SECTION 6 – REACTIVITY DATA

Stability: Stable. Product is not explosive.	Incompatibility: Alkaline materials, oxidizing agents and may attack mild steel.
Hazardous Decomposition Products: Hazardous fumes may accumulate in confined areas.	Hazardous Polymerization: Will not occur.
Conditions to Avoid: None	

SECTION 7 - SPILL OR LEAK PROCEDURES


Steps to be taken in case material is released or spilled: Small spill: Ventilate confined spaces. Keep product out of watercourses by diking.
Large Spill: Same as small spill.
Waste Disposal Method: Contact local authorities and comply with federal, state and local laws and regulations.

SECTION 8 – SPECIAL PROTECTION

Respiratory Protection: Use dust/mist respirator (high efficiency cartridges advised) if sanding or spraying. Use organic vapor cartridge respirator if TLV for solvent components may be exceeded (NIOSH approved). When using in confined areas, use air-fed hood.	Eye Protection: Splash goggles recommended or safety glasses with side shields are acceptable.
Protective Gloves: Impervious gloves are recommended to prevent skin contact.	Other Protective Equipment: Protective work clothing.
Ventilation: Use local exhaust when applying in confined areas. Provide adequate ventilation to maintain airborne concentrations below OSHA PELs.	



Water Tight Technologies, LLC
P.O. Box 899, Payson, AZ 85547



SECTION 9 – SPECIAL PRECAUTIONS OR OTHER COMMENTS

Storage/Handling:

Store in cool, dry, well ventilated facility. Store and use away from all sources of direct heat, sunlight and open flames. DO NOT FREEZE. Keep containers closed when not in use. Store in non-metallic containers.

Other Precautions:

Provide adequate ventilation and avoid prolonged or repeated contact with the skin. Wash with soap and water after contact.

Work/Hygienic Practices:

Maintain good personal hygiene practices. Wash contaminated clothing before reuse. Do not eat, drink, or smoke in work areas. Wash exposed skin before eating, drinking, smoking, or applying cosmetics.

SECTION 10 - TRANSPORTATION

Regulatory Agency:

Not regulated

Identification Number:

N/A

Proper Shipping Name:

N/A

Labels Required:

N/A

Hazard Classification:

N/A

Other Requirements:

N/A

Packing Group:

N/A

SECTION 11 – MISCELLANEOUS INFORMATION

Additional Comments:

Date of Previous MSDS:

Changes Since Previous MSDS:

Telephone Number for Additional Information:

(888) 269-2122

DISCLAIMER

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information is accurate, complete, or representative. Water Tight Technologies, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons if reasonable safety procedures are not followed.