




Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547



SECTION 1 – PRODUCT IDENTIFICATION

Product Name: SEBS Rust Inhibitor	Manufacturer's Name: Water Tight Technologies, LLC
Item Number: BRITE-n-EZ -- SEBSRI	Manufacturer's Address: P.O. Box 899, Payson, AZ 85547
24 Hour Emergency Telephone Number: CHEMTREC – United States 800-424-9300 ; International 202-483-7616 (collect)	HMIS Acute Hazard Rating: Health __, Flammability __, Reactivity __
Chemical Name/Synonyms: N/A	Chemical Family: Mixture

SECTION 2 – CHEMICAL COMPOSITION

Ingredient Components (chemical names) Common Names Hazardous components 1% or greater Carcinogens 0.1% or greater	%	Case No.	OSHA PEL-TWA	ACGIH TLV-TWA
Titanium Dioxide*		1343-67-7	5 mg / m³	5 mg / m³
Calcium Carbonate		1317-65-3	5 mg / m³	5 mg / m³
Silicon Dioxide (Amorphous)		112945-52-5	20 mppcf	5 mg / m³
Aromatic Solvent		64742-95-6	100 ppm	100 ppm
Styrene Butylene Block Copolymer	.1 - .2%	66070-58-4	N/A	N/A
Zinc Dibutyldithiocarbamate	12-13%	136-23-2	N/A	N/A
Polyalicyclic Resin		69430-35-9	N/A	N/A
Zinc Chromate	1 – 2%	37300-23-5	N/A	N/A


* Indicates toxic chemical subject to reporting requirements of sections 313 of Title III of 40 CFR 372.

SECTION 3 – PHYSICAL & CHEMICAL CHARACTERISTICS

Appearance/Odor: Yellow Liquid with Solvent Odor	Physical State: Liquid	Solubility in Water: Negligible
Boiling Point: 313° F - 572° F	Specific Gravity (H ₂ O=1) 1.1	Melting Point: N/A
Vapor Pressure: 2.7 mm Hg @ 68°F	Vapor Density: Heavier than air	Freezing Point: Not Established
VOC: 3.84 lb/gal. (460g/L)	Other Information: Evaporation rate – Slower than ether	Reactivity in Water: N/A



Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547



SECTION 4- FIRE & EXPLOSION HAZARD DATA


Flash Point: 114° F	Flammable Limits (in air): LEL: 0.5% ; UEL: 6.0%
Extinguishing Media: Water fog, carbon dioxide, foam or dry chemical extinguisher.	Fire Fighting Procedures: Positive pressure self-contained breathing apparatus (scba) and structural fighting protective clothing will provide limited protection.
Hazardous Decomposition Products: Fire may produce irritating or poisonous gases.	Special Fire & Explosion Hazards: Flammable/combustible material; may be ignited by heat, sparks or flames. Vapors may travel to a source of ignition and flash back. Containers may explode in heat of fire. Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.
Method Used: PMCC	Auto-Ignition Temperature: N/A

SECTION- 5 HEALTH HAZARD DATA

Effects of Overexposure: Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, fatigue, nausea, headache and possible unconsciousness. Prolonged or repeated contact with skin can cause moderate irritation, defatting and dermatitis.	Signs and Symptoms of Exposure: Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, fatigue, nausea, headache and possible unconsciousness. Eye contact can cause redness, tearing & blurred vision. Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Acute: Headache, dizziness, nausea and irritation	Chemical Listed as a Carcinogen (or Potential Carcinogen):
Chronic: Loss of appetite, nose bleeds.	National Toxicology Program: None I.A.R.C. Monographs: None OSHA: None
Emergency & First Aid Procedures: Symptoms of poisoning may even occur after several hours, therefore medical observation for at least 48 hours after the accident should occur.	
Eye Contact: Flush with water and call physician	
Skin Contact: Immediately wash with soap and water and rinse thoroughly.	
Inhalation: Remove to fresh air. Administer oxygen or artificial respiration, if necessary.	
Ingestion: Seek medical treatment.	
Primary Route of Entry: Inhalation, skin, eyes, ingestion.	



Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547



SECTION 6 – REACTIVITY DATA

Stability: Stable.	Incompatibility: Isolate from oxidizers, heat and open flame.
Hazardous Decomposition Products: Fire may produce irritating or poisonous gases.	Hazardous Polymerization: Will not occur.
Conditions to Avoid: Extreme heat, open flames.	

SECTION 7 - SPILL OR LEAK PROCEDURES


Steps to be taken in case material is released or spilled: Small spill: Ventilate confined spaces. Keep product out of watercourses by diking. Take up with sand or other noncombustible absorbent material and place into container for later disposal.	
Large Spill: Same as small spill. Dike far ahead of liquid spill for later disposal. Stop leak if you can without risk.	
Waste Disposal Method: Incinerate under safe conditions or dispose of in accordance with local, federal and state laws and regulations.	

SECTION 8 – SPECIAL PROTECTION

Respiratory Protection: Use respirator in confined areas.	Eye Protection: Splash goggles recommended or safety glasses with side shields are acceptable.
Protective Gloves: Impervious gloves are recommended to prevent skin contact.	Other Protective Equipment: Protective work clothing.
Ventilation: Local exhaust recommended.	



Water Tight Technologies, LLC
P.O. Box 899, Payson, AZ 85547



SECTION 9 – SPECIAL PRECAUTIONS OR OTHER COMMENTS

Storage/Handling:

Store in cool, dry, well ventilated facility. Store and use away from all sources of direct heat, sunlight and open flames. DO NOT FREEZE. Keep containers closed when not in use.

Other Precautions:

Provide adequate ventilation and avoid prolonged or repeated contact with the skin. Wash with soap and water after contact.

Work/Hygienic Practices:

Maintain good personal hygiene practices. Wash contaminated clothing before reuse. Do not eat, drink, or smoke in work areas. Wash exposed skin before eating, drinking, smoking, or applying cosmetics.

SECTION 10 - TRANSPORTATION

Regulatory Agency:

Identification Number:

N/A

Proper Shipping Name:

N/A

Labels Required:

N/A

Hazard Classification:

N/A

Other Requirements:

N/A

Packing Group:

N/A

SECTION 11 – MISCELLANEOUS INFORMATION

Additional Comments:

Date of Previous MSDS:

Changes Since Previous MSDS:

Telephone Number for Additional Information:

(888) 269-2122

DISCLAIMER

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information is accurate, complete, or representative. Water Tight Technologies, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons if reasonable safety procedures are not followed.