



**Water Tight Technologies, LLC**  
**P.O. Box 899**  
**Payson, AZ 85547**



**SECTION 1 – PRODUCT IDENTIFICATION**

Product Name: <b>Rubber to Rubber (Splice) Adhesive – Clear</b>	24 Hour Emergency Telephone Number: <b>800-424-9300 CHEMTREC</b>
Chemical Name/Synonyms: <b>Butyl Rubber Adhesive</b>	Manufacturer's Name: <b>Water Tight Technologies, LLC</b>
Chemical Family: <b>Mixture</b>	Manufacturer's Address: <b>P.O. Box 899</b> <b>Payson, AZ 85547</b>
Chemical Formula: <b>Not Established</b>	NFPA Acute Hazard Rating: <b>Health 2, Flammability 3, Reactivity 0</b> HMIS Acute Hazard Rating: <b>Health 2, Flammability 3, Reactivity 0</b>

**SECTION 2 – CHEMICAL COMPOSITION**

Ingredient Components (chemical names)	OSHA (1910.1200)	Case No.	% BY WEIGHT	OSHA PEL	ACGIH TLV
<b>Hexane</b>	<b>Acute Toxicity</b>	<b>110-54-3</b>	<b>14</b>	<b>500PPM</b>	<b>50PPM</b>
<b>Polyisocyanate</b>	<b>Irritant</b>	<b>28182-81-2</b>	<b>&lt;2</b>	<b>None Established</b>	
<b>Toluene</b>	<b>Acute/Chronic Toxicity</b>	<b>108-88-3</b>	<b>52</b>	<b>200PPM</b>	TLV 50PPM OSHA CEIL 300PPM ACGIH SKIN
<b>Xylene</b>	<b>Acute/Chronic Toxicity</b>	<b>1330-20-7</b>	<b>5</b>	<b>100PPM</b>	ACGIH STEL 150PPM <b>100PPM</b>
<b>Nonhazardous as per 29 CFR 1910.1200.</b>	<b>None</b>	<b>None</b>	<b>&gt;27</b>	<b>None Established</b>	

**SECTION 3 – PHYSICAL & CHEMICAL CHARACTERISTICS**

Appearance/Odor: <b>Clear viscous liquid, aromatic odor</b>	Physical State: <b>Liquid</b>	Solubility in Water: <b>Insoluble</b>
Boiling Point: <b>&gt;151° F</b>	Specific Gravity (Water =1) <b>.876</b>	Melting Point: <b>NA</b>
Vapor Pressure: <b>&lt;125 mm Hg @ 25° C</b>	Vapor Density (Air=1) <b>3.7</b>	Freezing Point: <b>Not Established</b>
Percent Volatiles: <b>70 %</b>	Evaporation Rate: <b>1.9-9.5 (Ether=1)</b>	Reactivity in Water: <b>NA</b>
pH (Full Strength) <b>Not Established</b>	pH (Recommended Dilution): <b>Not Established</b>	Refraction Index: <b>NA</b>

**Rubber to Rubber (Splice) Adhesive- Clear 1/5**  
 December 2007



Water Tight Technologies, LLC  
 P.O. Box 899  
 Payson, AZ 85547



**SECTION 4- FIRE & EXPLOSION HAZARD DATA**

Flash Point: <b>0° F (-17.8° C)</b>	Flammable Limits (in air): <b>LEL: 1.2%; UEL: 7%</b>
Extinguishing Media: <b>Dry chemical, carbon dioxide, water fog or foam. Do not use a direct water stream. Product will float and can re-ignite.</b>	Fire Fighting Procedures: <b>Use water spray to cool adjacent surfaces and fire exposed containers. Protect against inhalation of combustion products. Firefighters should wear full protective clothing including self-contained breathing apparatus to prevent inhalation of smoke and decomposition products. Toxic fumes and vapors may be involved.</b>
Hazardous Decomposition Products: <b>Carbon Dioxide, Carbon Monoxide, acrid smoke and irritating fumes.</b>	Special Fire & Explosion Hazards: <b>Flammable liquid. Vapors are heavier than air and can flow along surfaces to ignition sources and flash-back. Keep work areas free from open flames, sparks, hot metal surfaces and other sources of ignition. Ground objects prone to static electricity.</b>
Method Used: <b>TCC</b>	Auto-Ignition Temperature: <b>Not Established</b>

**SECTION- 5 HEALTH HAZARD DATA**

Permissible Exposure Limit: <b>Not Established</b>	Signs and Symptoms of Exposure: <b>Dizziness, nausea or vomiting. Difficulty in breathing. Sensitive individuals may exhibit eye, nose, throat or dermal irritation with prolonged exposure to processing fumes or vapors. Liquid can cause eye and skin irritation.</b>
Effects of Overexposure: <b>Medical Conditions Aggravated By Exposure. Toxic fumes may be released during fire. Exposure to fumes may aggravate pre-existing eye, lung, and skin conditions. Individuals with neurological diseases should avoid exposure to hexane. Individuals who are sensitized to Isocyanates, and those with pre-existing lung diseases or conditions, including non-specific bronchial hyperactivity or asthma, must avoid all exposure to Isocyanates.</b>	Primary Route of Exposure: <b>Skin absorption and inhalation. Toluene LC<sub>50</sub>: 8,000ppm/4hr, rat; Polyisocyanate LC<sub>50</sub>: &lt;1,150 mg/m<sup>3</sup>, rat; Xlyene LC<sub>50</sub>: 5,000 ppm/4hr, rat; Toluene LD<sub>50</sub>: 5 g/kg, rat; HDI LD<sub>50</sub>: 10 g/kg, rat; Xylene LD<sub>50</sub>: 4.3 g/kg, rat.</b>
Acute: <b>Irritation to eyes, lungs, and mucous membranes.</b>	
Chronic: <b>Excess exposure can cause CNS depression, headache, nausea, narcosis, and liver and kidney damage.</b>	



Water Tight Technologies, LLC  
 P.O. Box 899  
 Payson, AZ 85547



Acute Oral LD50 <b>&gt;8 ML/KG (Rat)</b>	Acute Dermal LD50 <b>&gt;4 ML/KG (Rat)</b>	Acute Inhalation LC50 <b>3400 PPM/4H (Rat)</b>
---	---	---

Emergency & First Aid Procedures:  
 Eye Contact:  
**Flush with water for 15 minutes and call physician.**  
 Skin Contact:  
**Clean with rubbing alcohol, followed by soap and water.**  
 Inhalation:  
**Remove to fresh air. Administer oxygen or artificial respiration, if necessary. Call physician.**  
 Ingestion:  
**Consult a Physician and advise as to the nature of the product. DO NOT INDUCE VOMITING.**  
 Primary Route of Entry:  
**Inhalation, Skin absorption.**

**SECTION 6 – REACTIVITY DATA**

Stability: <b>Stable at ambient temperatures and pressures</b>	Incompatibility: <b>Strong oxidizers, acids, bases.</b>
Hazardous Decomposition Products: <b>Toxic gases or vapors, such as oxides of carbon and nitrogen along with trace of HCL may be released during a fire.</b>	Hazardous Polymerization: <b>Will not occur</b>
Conditions to Avoid: <b>Avoid open flames and sparks. Avoid closed areas that restrict adequate ventilation.</b>	

**SECTION 7 - SPILL OR LEAK PROCEDURES**

Steps to be taken in case material is released or spilled:  
 Small spill:  
**Absorb using inert material. Use non-sparking tools. Transfer into secure containers for proper disposal. Use personal protective equipment as outlined below.**  
 Large Spill:  
**Same as small spill.**  
 Waste Disposal Method:  
**Dispose of as a hazardous waste in accordance with EPA/RCRA regulations 40CFR261 21(a) (1) Ignitability: D001**

**SECTION 8 – SPECIAL PROTECTION**

Respiratory Protection: <b>Use NIOSH-Certified respiratory protection for organic vapor if necessary.</b>	Eye Protection: <b>Impervious safety glasses recommended</b>
--	---



Water Tight Technologies, LLC  
 P.O. Box 899  
 Payson, AZ 85547



Protective Gloves: <b>Impervious gloves are recommended to prevent skin contact.</b>	Other Protective Equipment: <b>Under normal application conditions, protective glasses, gloves, and clothing are adequate.</b>
Ventilation: <b>Provide adequate ventilation to maintain airborne concentrations below OSHA PELs.</b>	

**SECTION 9 – SPECIAL PRECAUTIONS OR OTHER COMMENTS**

Storage/Handling: <b>Store in cool, dry, well ventilated facility. Store and use away from all sources of direct heat and ignition. Keep containers closed when not in use.</b>
Other Precautions: <b>Provide adequate ventilation and avoid prolonged or repeated contact with the skin. Wash with soap and water after contact.</b>
Work/Hygienic Practices: <b>Maintain good personal hygiene practices. Wash contaminated clothing before reuse. Do not eat, drink, or smoke in work areas. Wash exposed skin before eating, drinking, smoking, or applying cosmetics.</b>

**SECTION 10 - TRANSPORTATION**

Regulatory Agency: <b>U.S.A., DOT, IMO</b>	Identification Number: <b>UN1133</b>
Proper Shipping Name: <b>Adhesives</b>	Labels Required: <b>Flammable Liquid</b>
Hazard Classification: <b>3</b>	Other Requirements: <b>49 CFR 172.101 Adhesives, UN1133, IMDG Class 3.2, Pg. 3174, Flash Point -18° C</b>
Packing Group: <b>II</b>	

**Rubber to Rubber (Splice) Adhesive- Clear 4/5**  
 December, 2007



Water Tight Technologies, LLC  
P.O. Box 899  
Payson, AZ 85547



### SECTION 11 – MISCELLANEOUS INFORMATION

Additional Comments:

**None**

Date of Previous MSDS:

**March 21,2007**

Changes Since Previous MSDS:

**Update address Section I**

Telephone Number for Additional Information:

**(574) 293-9096**

### DISCLAIMER

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information is accurate, complete, or representative. Water Tight Technologies, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons if reasonable safety procedures are not followed.

**Rubber to Rubber (Splice) Adhesive- Clear 5/5**  
December, 2007